



Attorney Docket No. SON-856  
Date: March 5, 1996

ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Inventor: YUTAKA NAKATSU, SHIN IIMA, KAYOKO OHYOSHI and  
TOMOMI NAKAMURA

For: APPARATUS HAVING MEANS FOR PRINTING VIDEO  
SIGNALS OF VIDEO CAMERA ATTACHED THERETO

Enclosed are:

- ☒ Specification and Claim(s).
- ☒ Oath or Declaration. (Executed)
- ☒ FOUR sheet(s) of drawings.
- ☒ An assignment of the invention to SONY CORPORATION
- ☒ Certified copy of ONE priority application(s).
- ☐ Associate power of attorney.

The fee has been calculated as shown below:

CLAIMS AS FILED				
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE \$365°/\$750
TOTAL CLAIMS	6-20	0	x \$11° \$22	0
INDEP. CLAIMS	1-3	0	x \$38° \$78	0
Fee for Multiple Dependent claims \$120°/\$240				0
			TOTAL FILING FEE -----	750

☐ °Verified Statement claiming small entity status is enclosed.

☐ Charge \$\_\_\_\_\_ to Deposit Account No. 23-0978. A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees under 37 C.F.R. 1.16 or 1.17 which may be required during the entire pendency of this application, or to credit any overpayment, to Deposit Account No. 23-0978. A duplicate copy of this sheet is enclosed.


☒ A check in the amount of \$750 to cover the filing fee is enclosed.

☒ A check in the amount of \$40 to cover the recordal fee is enclosed. A duplicate copy of this sheet is enclosed.

☒ Applicant's undersigned attorney may be reached by telephone in our Washington D.C. Office at

(202) 955-4900.

All correspondence should be directed to our below listed address.

  
\_\_\_\_\_  
Ronald E. Kananen  
Reg. No. 24,104

MARKS & MURASE L.L.P.  
2001 L Street, N.W.  
Suite 750  
Washington, D.C. 20036



758.02-107 A  
08/610753

APPARATUS HAVING MEANS FOR PRINTING  
VIDEO SIGNALS OF VIDEO CAMERA ATTACHED THERETO

BACKGROUND OF THE INVENTION

The present invention relates to a video printer for printing a video signal of a video camera on a printing paper as a hard copy, and particularly to a video printer having a video printer housing portion with a video camera connected directly electrically thereto when the video printer is in use.

FIG. 1 of the accompanying drawings shows a manner in which a video printer is connected to a video camera in order to print a video picture of a video camera on a printing paper as a hard copy.

As shown in FIG. 1, a video printer 31 is connected to a video camera 32 through a signal input/output cord 33 from which video and audio signals, control signals, etc., are supplied to the video printer 31. The video printer 31 needs a television receiver 34 as a monitor receiver for displaying a video picture recorded by the video camera 32 on a picture screen of the television receiver in order for the user to visually confirm the manner in which the video printer 31 is operated. The television receiver 34 is connected to the video printer 31 through a signal input/output cord 35 accordingly.

In the system comprising the video printer 31, the video camera 32, and the television receiver 34, video picture from the video camera is displayed on the picture screen of the television receiver 34. However, when the user wants to watch

A, B  
a  
the video picture on the picture screen of the television receiver 34 in a step-by-step ~~picture, more of picture mode or picture more~~ or a still picture mode, the user has to operate the operation system of the video camera 32. When the user wants to print out video picture reproduced on the picture screen of the ~~television receiver 34~~ <sup>television receiver 34</sup> on a printing paper as a hard copy by the video printer 31, the user has to operate the operation system of the video printer 31 while visually confirming video picture displayed on the picture screen of the television receiver 34.

As described above, when the user wants to make a hard copy of video picture by the video printer 31, the user has to operate the two operation systems of the video printer 31 and the video camera 32 independently, and hence the user tends to operate the above two operation systems by mistake. Moreover, the television receiver 34 is indispensable for the user to visually confirm a picture entered into the video printer 31 and the manner in which the video printer 31 is operated.

#### SUMMARY OF THE INVENTION

In view of the aforesaid aspect, it is an object of the present invention to provide a video printer with a video camera detachably attached thereto in which the user can operate a video printer and a video camera by use of an operation system disposed on the video printer.

According to an aspect of the present invention, there is provided a video printer for printing a video picture recorded by a video camera on a printing paper as a hard copy, which comprises a video printer housing portion with a video

camera attached thereto, a signal input and output connection terminal disposed on the video printer housing portion for electrically connecting the video camera attached to the video printer housing portion to the video printer, and an operation system disposed on the video printer housing portion for operating the video camera.

a  
a  
a  
a  
08610758-030596  
The video camera is ~~of~~ a video camera with a liquid-crystal display monitor, ~~and~~ the video printer is operated while a video picture, <sup>is</sup> ~~a video picture~~ entered into the video printer, <sup>and</sup> ~~or~~ the manner in which the video printer is operated is visually confirmed on a picture screen of the liquid-crystal display monitor.

In the video printer with a video camera detachably attached thereto according to the present invention, the video camera is connected to the video printer housing portion through the connection terminals, thus enabling the video camera and the video printer to input and output signals therebetween. Then, the user can operate the video camera and the video printer by operating the operation system disposed on the video printer.

a  
In the video printer with a video camera detachably attached thereto according to the present invention, if a video camera connected to the video printer through the connection terminals is a video camera having a liquid-crystal display monitor, then the <sup>user becomes</sup> ~~user become~~ able to operate a video picture on the liquid-crystal display monitor of the video camera by operating the operation system of the video printer, and can print out a reproduced video picture on a printing paper as a

hard copy while visually confirming the video picture entered into the video printer by the liquid-crystal display monitor.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view illustrative of a manner in which a video printer, a video camera, and a television receiver are connected when the video printer is in use;

FIG. 2 is a perspective view illustrative of a manner in which a video printer and a video camera are not connected to each other;

FIG. 3 is a fragmentary plan view illustrative of signal input/output connection terminals attached to a video camera station of a video printer;

FIG. 4 is a perspective view illustrative of a manner in which a video camera is attached to a video printer; and

FIG. 5 is a fragmentary plan view illustrating a video camera operation system of a video printer.

#### DETAILED DESCRIPTION OF THE DRAWINGS

A video printer with a video camera detachably attached thereto according to the present invention will be described with reference to the drawings.

FIG. 2 is a perspective view illustrating a manner in which a video printer and a video camera are detached from each other when the video printer is not in use.

The video printer, generally denoted by reference numeral 1 in FIG. 2, includes a video printer housing portion 2 and a video camera station 3 provided at the rear upper surface of the video printer housing portion 2. The video camera

station 3 of the video printer 1 holds and electrically mechanically connects a video camera, which will be described later on, to the video printer 1. The video camera station 3 includes a signal input/output terminal 4 composed of a plurality of contact groups as a connection terminal, and a pair of guide rails 5, 5 for slidably guiding the video camera from one side to the video camera station 3.

FIG. 3 is a plan view illustrating the signal input/output terminal 4 in detail in an enlarged scale.

As shown in FIG. 4, the contact terminal 4 comprises contact members 4a through 4t each having a spring action, and the contact members 4a through 4t are arranged in two columns, by way of example. Names of respective contact members 4a through 4t will be described below.

The contact member 4a is referred to as "S-terminal (Y luminance) OUT", the contact member 4b is "S-terminal (chroma) OUT", the contact member 4c is "video-OUT", the contact member 4d is "video-GND", the contact members 4e, 4f are "dead terminals", the contact member 4g is "audio-GND", the contact member 4h is "VTR control signal terminal", the contact member 4j is "VTR communication GND", the contact member 4k is "dead terminal", the contact members 4l, 4m, 4n and 4o are "power supply GND", the contact members 4p and 4q are "dead terminals", the contact members 4r and 4s are "power supplies", and the contact member 4t is "device detection signal terminal".

Referring back to FIG. 2, the video camera 6 applied to the present invention includes a liquid-crystal display

InsA'  
a  
monitor 7. ~~The video camera 6 has on its bottom surface formed~~  
an electrode terminal (not shown) which electrically contacts  
~~with~~ the signal input/output terminal 4 of the video camera  
station 3 and a guide portion (not shown) which is engaged with  
the guide rails 5, 5 of the video camera station 3 for slidable  
movement.

FIG. 4 is a perspective view illustrating a manner in  
which the video camera 6 is attached to the video camera station  
3 of the video printer 1, the video camera station 3 and the  
video camera 6 are electrically connected, and also the video  
camera station 3 and the video camera 6 are mechanically jointed  
in the locked state. In FIG. 4, when the user wishes to detach  
the video camera 6 from the video camera station 3, the user can  
release the locked state of the video camera 6 and detach the  
video camera 6 from the video printer housing portion 2 by  
depressing a button 3a on the video camera station 3.

An operation system 8 for operating the video camera 6  
and an operation system 9 for operating the video printer 1 are  
disposed on the front upper surface side of the video printer  
housing portion 2.

The operation system 8 for operating the video camera  
6 comprises a shuttle ring 10 for fast-forwarding or rewinding a  
video picture displayed on the picture screen of the liquid-  
crystal display monitor 7 of the video camera 6, a play button  
11 integrally disposed at the central portion of the shuttle  
ring 10 for playing back a video picture on the picture screen  
of the liquid-crystal display monitor 7, and a stop button 12



integrally disposed at a part of the play button 11 for stopping the operation of the video camera 6. A pause button 13 is disposed in the vicinity of the shuttle ring 10 for temporarily placing a video picture in the state of a still picture.

The operation system 9 for operating the video printer 1 comprises a memory button 14 for storing a video picture of the video camera 6 in a memory (not shown) of the video printer 1, a memory picture button 15 for accessing the video picture stored in the memory of the video printer 1, an input picture button 16 for entering video data indicative of video picture into the memory of the video printer 1 and a print button 17 for energizing the video printer 1. The printer housing 2 includes a variety of setting buttons for setting various print conditions during printing, although not shown. When the video printer 1 is not in use, these setting buttons are covered with a lid 18.

As shown in FIG. 2, a print ink ribbon cassette loading portion 19 and video signal input and output terminals 20 are formed <sup>on a side</sup> ~~on side~~ portion of the video printer housing ~~portion 2~~ <sup>portion 2</sup> ~~portion 20~~. A printing paper storage tray loading slot 21 and a power-supply switch 22 are disposed on the front portion of the video printer housing portion 2.

When the video printer 1 thus arranged ~~so far~~ is in use, the video camera 6 is mechanically attached to the video camera station 3 of the video printer housing portion 2, whereby the signal input and output terminal 4 of the video printer 1 and the electrode terminal (not shown) of the video camera 6 are

connected electrically. Thus, the user can operate the video camera 6 by operating the operation system 8 of the video printer 1.

Specifically, when the user operates the play button 11 on the operation system 8, a video picture that has been recorded by the video camera 6 can be reproduced on the liquid-crystal display monitor 7. Moreover, when the user rotates the shuttle ring 10 in the clockwise direction, a reproduced picture is moved in the fast-forward mode. When the user rotates the shuttle ring 10 in the counter-clockwise direction, a reproduced picture can be moved in the rewind mode. Furthermore, when the user operates the pause button 13, a reproduced picture can be placed in the pause mode.

Accordingly, when the user prints out a video picture by the video printer 1, the user selects a video picture to be printed while operating the operation system 8 for the video camera 6, and the user can print out a selected video picture by operating the video printer 1 at its operation system 9 disposed near the operation system 8.

As described above, in the video printer 1 according to the present invention, the user can easily carry out a series of operations by operating the video camera operation system 8 disposed on the video printer 1 and the video printer operation system 9 also disposed on the video printer 1.

Further, the user can visually easily confirm the manner in which the video printer 1 is operated and a video picture inputted to the video printer 1 from a picture

reproduced on the liquid-crystal display monitor 7 of the video camera 6. Therefore, the user can be prevented from operating the operation system 8 or 9 by mistake.

Furthermore, the video camera 6, the video printer 1 and the television receiver serving as the monitor receiver need not be connected via troublesome cords unlike the prior art. In addition, the television receiver need not be used as a monitor receiver.

In the above embodiment, the operation system 8 for the video camera 6 and the operation system 9 for the video printer 1 are disposed adjacent to each other on the video printer 1. However, the principle of the present invention is not limited thereto, and may similarly be applied to the arrangement where the operation systems 8 and 9 are spaced apart from each other so long as the video camera operation system 8 is disposed on the video printer housing portion 2.

As described above, since the video printer with the video camera detachably attached thereto includes the video printer housing portion with the signal input and output connection terminal electrically connected to the video camera and the video camera operation system disposed thereon, the user can easily operate the video camera on the video printer housing portion side.

~~Further, the video camera, the video printer and the television receiver serving as the monitor receiver need not be connected via troublesome cords unlike the prior art. In addition, the television receiver need not be used as a monitor~~

~~a~~  
receiver.

Furthermore, the user can visually easily confirm the manner in which the video printer is operated and a video picture inputted to the video printer from a picture reproduced on the liquid-crystal display monitor of the video camera. Therefore, the user can be prevented from wrongly operating the operation system.

Having described a preferred embodiment of the invention with reference to the accompanying drawings, it is to be understood that the invention is not limited to that precise embodiment and that various changes and modifications could be effected therein by one skilled in the art without departing from the spirit or scope of the invention as defined in the appended claims.

What is claimed is:

1. A video printer for printing a video picture recorded by a video camera on a printing paper as a hard copy, comprising:

a video printer housing portion with a video camera attached thereto;

a signal input and output connection terminal disposed on said video printer housing portion for electrically connecting said video camera attached to said video printer housing portion to said video printer; and

an operation system disposed on said video printer housing portion for operating said video camera.

2. A video printer according to claim 1, wherein said video camera is ~~of a~~ video camera with a liquid-crystal display monitor, ~~and~~ said video printer is operated while a video picture <sup>is</sup> ~~a video picture~~ entered into the video printer <sup>and</sup> ~~or the~~ manner in which the video printer is operated is visually confirmed on a picture screen of said liquid-crystal display monitor.

3. A video printer according to claim 1, wherein said video printer housing portion has a pair of guide rails formed at its portion to which said video camera is attached, and said guide rails guide an electrode terminal disposed on a bottom surface of said video camera to the position at which said

electrode terminal comes in contact with said input and output connection terminal. *D*

*sub B2* 4. A video printer according to claim 1, wherein said video camera operation system includes a shuttle ring for displaying a video picture in the fast-forward mode or rewind mode on the picture screen of said liquid-crystal display monitor.

5. A video printer according to claim 1, wherein said video camera operation system includes memory operation means for storing video data indicative of a video picture recorded by said video camera in a memory of said video printer.

6. A video printer according to claim 1, wherein said video camera operation system includes input operation means for entering video data indicative of video picture in a memory of said video printer. *D*

03610758-030596

*add B3*

08/610758


ABSTRACT OF THE DISCLOSURE

a

A video printer (1) <sup>comprises</sup> ~~comprising~~ a video printer housing portion (2), and a video camera station (3) disposed on a rear upper portion of the video printer housing portion (2) and having a signal input and output connection terminal (4). A video camera (6) with a liquid-crystal display monitor (7) is electrically connected to the connection terminal (4), and attached to the video printer (1) at its video camera station (3) so that, when the video printer (1) is in use, a user can operate the video camera (6) and the video printer (1) by operating operation systems (8), (9) disposed on the video printer (1) while visually confirming a picture displayed on a picture screen of the liquid-crystal display monitor (7).

00610758-030555

FIG. 1








FIG. 3




FIG. 4





FIG. 5



# DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

## English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

APPARATUS HAVING MEANS FOR PRINTING VIDEO SIGNALS OF VIDEO CAMERA ATTACHED THERETO  
the specification of which

(check one)

X is attached hereto.

☐ was filed on \_\_\_\_\_ as

Application Serial No. \_\_\_\_\_

and was amended on \_\_\_\_\_  
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent of inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s) Priority Claimed

<u>P07-047577</u>	<u>Japan</u>	<u>07 March 1995</u>	X	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
 <u>                    </u>	 <u>                    </u>	 <u>                    </u>	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
 <u>                    </u>	 <u>                    </u>	 <u>                    </u>	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

<u>                    </u>	<u>                    </u>	<u>                    </u>
(Application Serial No.)	(Filing Date)	(Status)
		(patented, pending, abandoned)
 <u>                    </u>	 <u>                    </u>	 <u>                    </u>
(Application Serial No.)	(Filing Date)	(Status)
		(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

## English Language Declaration

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Richard Linn, Registration No. 25,144, Ronald P. Kananen, Registration No. 24,104, Michael D. Bednarek, Registration No. 32,329, George T. Marcou, Registration No. 33,014, George C. Beck, Registration No. 38,072, Richard T. Peterson, Registration No. 35,320, and Jeffrey L. Thompson, Registration No. 37,025.

Send Correspondence to:

Ronald P. Kananen  
MARKS & MURASE L.L.P.  
Suite 750  
2001 L Street, N.W.  
Washington, D.C. 20036

Direct telephone calls to:

Ronald P. Kananen  
(202) 955-4900

Full name of sole or FIRST inventor <u>YUTAKA NAKATSU</u>	
First Inventor's signature <u>Y. Nakatsu</u>	<u>22 Feb 1996</u> Date
Residence <u>Tokyo, Japan</u> <u>JPX</u>	
Citizenship <u>Japanese</u>	
Post Office Address <u>c/o Sony Corporation 7-35, Kitashinagawa 6-Chome,</u> <u>Shinagawa-Ku, Tokyo, Japan</u>	
<u>200</u>	
Full name of SECOND joint inventor <u>SHIN IIMA</u>	
Second Inventor's signature <u>S. Iima</u>	<u>Feb. 22, 1996</u> Date
Residence <u>Tokyo, Japan</u> <u>JPX</u>	
Citizenship <u>Japanese</u>	
Post Office Address <u>c/o Sony Corporation 7-35, Kitashinagawa 6-Chome,</u> <u>Shinagawa-Ku, Tokyo, Japan</u>	

Full name of THIRD inv KAYOKO OHYOSHI

Third Inventor's signature

K. Ohyoshi

23. Feb. 1996 Date

Residence Tokyo, Japan

Citizenship Japanese

Post Office Address c/o Sony Corporation 7-35, Kitashinagawa 6-Chome,  
Shinagawa-Ku, Tokyo, Japan

Jpx

400

Full name of FOURTH joint inventor TOMOMI NAKAMURA

Fourth Inventor's signature

T. Nakamura

22. Feb. 1996 Date

Residence Tokyo, Japan

Citizenship Japanese

Post Office Address c/o Sony Corporation 7-35, Kitashinagawa 6-Chome,  
Shinagawa-Ku, Tokyo, Japan

Jpx